

Find your product and get support

FAQ

Driver

User Manual

Europe

<https://aoc.com/uk/support>

Россия

<https://aoc.com/ru/support>

Australia

https://au.aoc.com/user_manual

Hong Kong S.A.R.

https://hk.aoc.com/user_manual

中國台灣

https://tw.aoc.com/user_manual

Indonesia

https://id.aoc.com/user_manual

日本

https://jp.aoc.com/user_manual

한국

https://kr.aoc.com/user_manual

Malaysia

https://my.aoc.com/user_manual

Myanmar

https://mm.aoc.com/user_manual

New Zealand

https://nz.aoc.com/user_manual

Philippines

https://ph.aoc.com/user_manual

Singapore

https://sg.aoc.com/user_manual

ประเทศไทย

https://th.aoc.com/user_manual

Việt Nam

https://vn.aoc.com/user_manual

Middle East

https://me.aoc.com/user_manual

South Africa

https://za.aoc.com/user_manual

Brasil

<https://aoc.portaltpv.com.br/>

India

<https://aoc.com/in-en/support>

US

<https://aoc.com/us/support>

Canada

<https://aoc.com/ca-en/support>

HDMI

HIGH DEFINITION MULTIMEDIA INTERFACE

Product information for EU/UK Energy

XXXXXXXXXXXX

QUICK
START
GUIDE

U32U3CV
MONITOR

AOC.COM

©2024 AOC. All rights reserved

AOC

Monitor

Stand

Base

*

Quick Start Guide

Warranty Card

Screwdriver

Power Cable

*
HDMI Cable

*
DP Cable

*
USB C-C Cable

*
USB C-C/A Cable

*Different according to countries/regions
Display design may differ from that illustrated

1

2

3

4

General Specification

Panel	Model Name	U32U3CV	
	Driving System	TFT Color LCD	
	Viewable Image Size	80.0cm diagonal (31.5" Wide Screen)	
	Pixel Pitch	0.18159mm(H) x 0.18159mm(V)	
Others	Horizontal Scan Range	30k-140kHz	
	Horizontal Scan Size(Maximum)	697.3mm	
	Vertical Scan Range	23-75Hz	
	Vertical Scan Size(Maximum)	392.2mm	
	Max Resolution	3840x2160@60Hz	
	Plug & Play	VESA DDC2B/CI	
	Power Source	100-240V~ 50/60Hz 3.0A	
	Power Consumption	Typical (default brightness and contrast) Max. (brightness =100, contrast =100) Standby mode	46W ≤ 215W ≤ 0.3W
Physical Characteristics	Dimensions(with stand)	714.4x(459.3~609.3)x258.6mm (WxHxD)	
	Net Weight	8.46kg	
	Connector Type	HDMIx2, DisplayPort, RJ-45, Earphone, USB C1: Video,PD 96W USB C2: Upstream USB C (Side): Power supply up to 15W USB-Ax4 (include 1 fast charge)	
	Signal Cable Type	Detachable	
Environmental	Built-In Speaker	3Wx2	
	Temperature	Operating	0°C~40°C
		Non-Operating	-25°C~55°C
	Humidity	Operating	10%~85% (Non-Condensing)
		Non-Operating	5%~93% (Non-Condensing)
	Altitude	Operating	0m~5000m (0ft~16404ft)
		Non-Operating	0m~12192m (0ft~40000ft)