

NEOZED FUSE LINK 400V GL, SIZE D02, 25A IN FOLDING BOX  
WITH TIN-PLATED CONTACT-CAPS



Figure similar

| Model                                                          |                                 |
|----------------------------------------------------------------|---------------------------------|
| Product brand name                                             | SETRON                          |
| Product designation                                            | NEOZED fuse link                |
| Design of the product                                          | With tin-coated contact caps    |
| Product variations                                             | Pack of 10                      |
| Design of the fuse link                                        | NEOZED fuse link                |
| General technical data                                         |                                 |
| Size of fuse system / acc. to DIN EN 60269-1                   | D02                             |
| Operating class of the fuse link                               | gG                              |
| Supply voltage                                                 |                                 |
| • at AC / rated value                                          | 400 V                           |
| • at DC                                                        | 250 V                           |
| Protection class IP                                            | IP20, with connected conductors |
| Switching capacity current / acc. to IEC 60947-2 / rated value | 50 kA                           |
| Dissipation                                                    |                                 |
| Power loss [W]                                                 |                                 |

|                                                                              |       |
|------------------------------------------------------------------------------|-------|
| • for rated value of the current / at AC / in hot operating state / per pole | 1.7 W |
| • maximum                                                                    | 1.7 W |
| Current / at AC / rated value                                                | 25 A  |

| Main circuit                    |       |
|---------------------------------|-------|
| Operating voltage / rated value | 400 V |
| Operating current / rated value | 25 A  |

| Appearance                                                                               |                                  |
|------------------------------------------------------------------------------------------|----------------------------------|
| Color coding of the fuse link                                                            | Yellow                           |
| Maximum short-circuit current breaking capacity (I <sub>cu</sub> ) / at AC / rated value | 50 kA                            |
| Mounting position                                                                        | Any, preferably vertical         |
| Net weight                                                                               | 12 g                             |
| Environmental category                                                                   | Up to 45°C at 95 % rel. humidity |

| Certificates                                    |   |
|-------------------------------------------------|---|
| • Reference identifier / acc. to DIN EN 61346-2 | F |
| • Reference identifier / acc. to DIN EN 81346-2 | F |

| General Product Approval | Declaration of Conformity | Test Certificates |
|--------------------------|---------------------------|-------------------|
|--------------------------|---------------------------|-------------------|



ÖVE



VDE



EG-Konf.

[Miscellaneous](#)

[Type Test  
Certificates/Test  
Report](#)

[Special Test  
Certificate](#)

#### other

[Environmental  
Confirmations](#)

#### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<http://www.siemens.com/lowvoltage/catalogs>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=5SE2325>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/5SE2325>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_en.aspx?mlfb=5SE2325](http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=5SE2325)

**CAX-Online-Generator**

<http://www.siemens.com/cax>

**Tender specifications**

<http://www.siemens.com/specifications>

